



Part # 288/DL

The new Dual Mixer is a sink mixer and filtered water tap all-in-one and offers new levels of function and simplicity in the kitchen.

Imagine just one innovative mixer performing two essential functions for that clean, minimalistic look. With ample supply of sparkling, fresh tasting water for drinking, food preparation, cooking etc. at the flick of a lever.

This stylish mixer comes in bright, mirror polished chrome and features ceramic disc valve technology for a smooth, durable action. Precision built in Australia using the best materials, it complies with Australian Standards AS/NZS 3718 and the WELS regulation, carrying a five year guarantee.

Installation and Operation

Fit the mixer through a sink or benchtop. Operation is as normal by means of the main handle and water flows from the aerator at the end of the swivel spout. The valve incorporates an anti-scald adjustment ring and a flow limiting screw.

A filter system connects to mains cold water and connects easily to the third braided hose. Filtered water is controlled by the pin knob at the base of the Dual Mixer and flows from the second outlet.

Technical Specifications

Tap Hole Size	35-45mm
Bench thickness:	45mm max.
Sink thickness:	0.8mm min.
Supply Pressure:	100-1000kPa (500kPa optimum)
Hot Water Temp:	70°C
Cold Water Temp:	3-40°C
Flow Rate, Mixer:	Nom, 9Lpm
Flow Rate, Filter Tap:	Nom, 5Lpm
Supply Fittings:	½" BSP

Note: Cold supply to be fitted with with approved mini stop incorporating removable inline strainer. Purification systems must incorporate a Pressure limitin, backflow prevention and water hammer arresting valve.

WaterMark certified to
AS/NZS 3718
AS/NZS 4020
AS/NZS 6400
and is built in Australia
License No. WMK2456

