

PENTEK DFX SERIES DIAMOND FLOW CARTRIDGES

DUAL-TECHNOLOGY FILTRATION



DFX Series Diamond Flow cartridges are a unique, premium cartridge that utilizes several of the Pentair core competencies by merging technologies into one cartridge in order to bring customers a quality product. Diamond Flow Series cartridges offer the effective chlorine taste & odor reduction found in traditional Pentek[®] carbon blocks, joined with the superior sediment reduction to resist premature plugging. These dual purpose cartridges are well-suited for a wide range of applications.

FEATURES/BENEFITS

High dirt-holding capacity maximizes utilization of the carbon block*

Chlorine taste & odor reduction combined with superior sediment reduction*

Available in a 10-micron rating

Available in 10" & 20" lengths

Available in Standard & Big Blue[®] Size

Low pressure drop

New product design with Pentair branding

Twice as resistant to particulate plugging than standard carbon blocks*

MATERIALS OF CONSTRUCTION

Exterior Filter Media:
Polypropylene Polyspun

Interior Filter Media:
Carbon Block

Endcaps: Polypropylene

Gaskets: Buna-N

Temperature Rating: 40°-125°F



The DFX Series Diamond Flow cartridges are Tested and Certified by NSF International to NSF/ANSI Standard 42 for material requirements only.

*Based on manufacturer's internal testing.

SPECIFICATIONS AND PERFORMANCE

| PART NUMBER | MODEL | MAXIMUM DIMENSIONS | RATING (NOMINAL) | INITIAL ΔP (PSI) @ FLOW RATE (GPM) | CHLORINE TASTE & ODOR REDUCTION @ FLOW RATE |
|-------------|-------------|--|------------------|--|---|
| 655130-43 | DFX-CB-10 | 2.89" x 9.81" (73.406 mm x 249.174 mm) | 10 μ | 1.0 psi @ 1.0 gpm (0.07 bar @ 3.8 Lpm) | 2,500 gal @ 1.0 gpm (9,464 L @ 3.8 Lpm) |
| 655148-43 | DFX-CB-20 | 2.89" x 20.035" (73.406 mm x 508.89 mm) | 10 μ | 1.0 psi @ 2.0 gpm (0.07 bar @ 7.6 Lpm) | 5,000 gal @ 2.0 gpm (18,927 L @ 7.6 Lpm) |
| 655151-43 | DFX-CB-BB | 4.63" x 9.81" (117.60 mm x 249.174 mm) | 10 μ | 1.0 psi @ 2.0 gpm (0.07 bar @ 7.6 Lpm) | 15,000 gal @ 2.0 gpm (56,781 L @ 7.6 Lpm) |
| 655152-43 | DFX-CB-20BB | 4.63" x 20.035" (117.60 mm x 508.89 mm) | 10μ | 1.0psi @ 4.0 gpm (0.07 bar @ 15.14 Lpm) | 30,000 gal @ 4.0 gpm (113,562 L @ 15.14 Lpm) |



5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2017 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com.

Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

247684 REV F AP17