

SWING & TWIST FILTRATION SYSTEMS



The thirst quenchers!



- ✓ Automatic shut off filter head makes filter replacements safe and easy
- ✓ Compact design allows maximum use of space under sinks or behind water dispensers
- ✓ Cost saving - Reduces servicing costs by saving time on filter changes
- ✓ Easy cartridge replacement - No housing spanners or tools required
- ✓ O'ring is on the filter - New O'rings with every filter change
- ✓ Single, twin or triple filtration systems available.



SWING & TWIST FILTRATION SYSTEMS

FILTER CARTRIDGE OPTIONS

SEDIMENT CARTRIDGE – F-PNP-10-SED	HOLLOW-FIBER – F-PNP-10-HOL
Polypropylene pre filter for the removal of dirt sediment, rust and particles.	Superior micro-fine membrane for the removal of bacteria.
Flow rate 2L per minute	Flow rate 2L per minute
Filter replacement – 1900L or 6 months. Which ever occurs first.	Filter replacement – 1900L or 6 months. Which ever occurs first.
5 micron	0.3
Operating Temperatures: 4-38°C	Operating Temperatures: 4-38°C

CARBON BLOCK – F-PNP-10-CARB-5MIC	ULTRA CARBON BLOCK – F-PNP-10CARB-1MIC
Silver impregnated carbon block for chemical, taste and odour removal.	Silver impregnated carbon block for chemical, taste and odour removal.
Flow rate 2L per minute	Flow rate 2L per minute
Filter replacement – 1900L or 6 months. Which ever occurs first.	Filter replacement – 1900L or 6 months. Which ever occurs first.
5 micron	1 Micron
Operating Temperatures: 4-38°C	Operating Temperatures: 4-38°C

PHOSPHATE – F-PNP-10-PHOS
Removes scale build up in coffee machines, refrigerators, hot water boilers, water cooler, etc
Granule activated carbon/phosphate
Flow rate 2L per minute
Filter replacement – 1900L or 6 months. Whichever occurs first.
Operating Temperatures: 4-38°C

NOTES

Filter should be pre flushed prior to attaching to equipment or after long periods of inactivity.

Do not use with water that is microbiologically unsafe or of unknown quality.

Turn water off to filter system if not in use for extended periods.

Automatic shut off valve automatically shuts off water supply to the system when filter is removed.

Filter life can vary depending on water quality and demand.

A 350Kpa pressure limiting valve **MUST** be installed.

Installation of your water filter system must only be carried out by a licensed technician and all aspects of the installation must comply with current local authority standards and regulations.

DIMENSIONS CENTIMETRES

	HEIGHT	WIDTH	DEPTH
Single	31	8	9
Twin	31	15.5	9
Triple	31	24	9



Distributed by...

Waterworks Australia

ABN 91 902 793 936

48 Neumann Road Capalaba Queensland 4157

Phone (07) 3390 3777 • Fax (07) 3390 1766

Email sales@waterworksaustralia.com

www.waterworksaustralia.com

As part of Waterworks Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.