# D19/SD19 SERIES



The thirst quenchers!



- ✓ Stylish high gloss black & stainless look cabinet
- ✓ Available in Hot/Cold or Cool/Cold
- ✓ Hygienic push taps
- √ 3.3 litre stainless steel cold tank
- ✓ Connects to mains water supply
- ✓ Compatible with most Inline Filter Systems
- ✓ Access plate on the side of SD19C
- √ 36 Month Comprehensive Warranty



PROVEN
QUALITY &
PERFORMANCE
FOR OVER 20
YEARS!



# D19/SD19 SERIES

# **GENERAL FEATURES**

With its high gloss front, brushed steel sides and stylish slim design, the D19 series cooler is perfect for any home or office.

**COLD TANK:** 3.3 litre type 304 stainless steel for superior chilling. The highly polished surface is easy to clean and maintain.

**HOT TANK:** 1.8 litre type 304 stainless steel with 500 watt sheathed heater ensures temperature control. On/off switch is easily accessible at the back of the unit.

**CABINET:** Black high gloss front with brushed steel silver sides. The top and front panels are moulded ABS plastic, the side panels are high polymer coated steel.

**TAPS:** NSF approved and hygienic durable polypropylene push taps with self-closing design and fast flow. Hot safety tap comes as standard on hot/cold model.

**FLOAT ASSEMBLY:** Dual float system maintains the water level and shuts off when full.

#### **OPTIONAL EXTRAS**

PNP FILTER SYSTEM: The Waterworks™ PNP filter range is available in single, twin or triple. With the swing & twist design and automatic water shutoff, filter changes are simple, no need for tools or to turn off the mains water.

**CD WHITE OR BLACK:** Our cup dispensers come in black or white to match either colour unit. Waterworks™ paper & plastic cups are designed to fit our dispensers.

### **SPECIFICATIONS**

**REFRIGERATION:** Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

**ELECTRICAL:** Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

**CONDENSER:** Quietly operating, air cooled with no moving parts.

# **PERFORMANCE**

Tap 1 Approx. 4-10°C Tap 2 Room Temperature Hot tap Approx. 84-89°C

ROOM TEMP °C	21	27	32			
150ML CUPS/HR 10°C	22	17	13			
LITRES/HR AT 10°C	3.2	2.6	2			
HOT WATER DELIVERY: 15 x 170ml cups per hour						

<sup>\*</sup>Intermittent use only, continuous use will result in reduced performance.

#### SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
D19C	17kg	D19CH	19kg	29cm	34cm	100cm
SD19C	16kg	SD19CH	18kg	29cm	51cm	53cm

#### WARRANTY

The Waterworks™ D19 series is covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage, for the period of 36 months from the date of original sale.



Distributed by...

Aqua Wise 07 54424788 sales@aquawise.com.au www.aquawise.com.au